



- Roof Motors: 1.1 amps (each)
  - Screen Motor: 1.1 amps (each)
  - LED Lights: <0.1 amps
- Pod is fitted with a 3 core (live, neutral, earth) cable exiting the nominated corner post/cross beam that needs connecting to a standard switched fuse spur/socket fitted with a 13amp fuse.
- Drainage is via ø50 downpipes in nominated corner posts. One drainage point (corner post) is required per 15m<sup>2</sup> roof surface area

All dimensions are shown in millimetres unless otherwise stated



Tel: 0344 800 1947

info@cbsolarshading.co.uk    www.cbsolarshading.co.uk

HEAD OFFICE, FACTORY & SHOWSITE  
Woodhall Business Park, Sudbury, Suffolk, CO10 1WH

It is Caribbean Blinds UK Ltd policy to continuously develop and improve our products. We therefore reserve the right to modify or change the detail/design at our discretion and without prior notice. This drawing is the copyright and sole property of Caribbean Blinds UK Ltd. The design/information is private and confidential. It must not be copied, exhibited or communicated to third parties for any purpose other than that for which it was issued without the written consent of Caribbean Blinds UK Ltd.

Drawing Name: Prestige Pod Arrangement & Mounting		
Drawing Number: CB/O LP/PRE/AM	Rev: A	
Date: 13/12/2024	Scale: NTS	Drawn By: CB